This listing of claims will replace all prior versions, and listings, of claims in the present

Docket No.: 0445-0340P

application.

Listing of Claims:

1-5. (Canceled)

6. (Previously Presented) The disposable diaper according to claim 7, wherein two

portions on opposite sides of a centerline dividing the length of the diaper in equal halves have a

saturated absorption capacity ratio of from 45/55 to 55/45.

7. (Previously Presented) A disposable diaper for babies and infants in the standing or

crawling position, said disposable diaper comprising a liquid permeable topsheet, a liquid

impermeable backsheet, a liquid retentive absorbent member interposed between the topsheet

and the backsheet, and a fastening tape provided on each side edge of one of a pair of

longitudinal end sections thereof and having a pair of standing gathers and a pair of leg gathers

each formed by fixing respective elastic members in each of a pair of longitudinal side portions

thereof, wherein

a smallest width of the crotch section is 100 to 240 mm.

a ratio of a distance W11 between a pair of fixed ends of the pair of standing gathers

measured at the smallest width of a crotch section to a distance W12 between each elastic

member that is arranged most outward in each of the respective leg gathers, and with both

2 of 11 JWB/ETP

distances being measured at the smallest width of the crotch section, W11/W12, is from 0.67 to 0.81.

Docket No.: 0445-0340P

a distance W13 between each of the fixed ends of the pair of standing gathers and each of the elastic members that are arranged most outward in the pair of leg gathers as measured at the smallest width of the crotch section is smaller than a width W14 of the standing gathers on each side as measured at the smallest width of the crotch section,

the standing gathers being formed by fixing an elastic member having a fixing extension ratio of 100% to 300%, and

the standing gathers on each longitudinal side portion having tensile characteristics, which as measured in a state of the gathers not being fixed to the diaper, wherein the tensile load required to extend the standing gathers to an effective extension ratio, which is 30% lower than the fixing extension ratio, is from 20 to 120 gf, and the rate of increase of the tensile load required to extend from an extension ratio of 20% to the effective extension ratio is 1.0 gf/% or lower.

- 8. (Original) The disposable diaper according to claim 7, wherein the ratio W11/W12 is in the range of from 0.67 to 0.81 over an area extending at least 50 mm in a length direction of the diaper.
- 9. (Original) The disposable diaper according to claim 7, wherein the distance W13 is smaller than the width W14 over an area extending at least 50 mm in a length direction of the diaper.

10. (Previously Presented) A disposable diaper comprising a liquid permeable topsheet,

Docket No.: 0445-0340P

a liquid impermeable backsheet, a liquid retentive absorbent member interposed between the

topsheet and the backsheet, and a fastening tape provided on each side edge of one of a pair of

the longitudinal end sections thereof, and a landing zone where the fastening tape can be fixed on

an outer side of the other longitudinal end section of the pair, and a laterally extensible side part

provided on each side area of a below-waist portion of the longitudinal end section having the

fastening tapes, wherein

a tensile load required to extend the below-waist portion of the longitudinal end section

having the fastening tapes in the diaper width direction to an extension ratio that is 30% lower

than a maximum extension ratio is from 80 to 500 gf,

a smallest width of a crotch section of the diaper is from 100 to 240 mm,

a region having the absorbent member in the crotch section has a flexural stiffness of

from 3 to 25 gf/50 mm in a width direction of the diaper, and

the disposable diaper weighs from 20 to 40  $\ensuremath{\mathrm{g}}.$ 

11. (Original) The disposable diaper according to claim 10, wherein the crotch section

possesses a width that is in a range of from 100 to 240 mm in an area extending at least 50 mm in

a length direction of the diaper.

12. (Canceled)

4 of 11 JWB/ETP

Application No. 10/626,547

Art Unit 3761

After Final Office Action of June 14, 2006

13. (Original) The disposable diaper according to claim 10, wherein two portions on

Docket No.: 0445-0340P

opposite sides of a centerline dividing the length of the diaper in equal halves have a saturated

absorption capacity ratio of from 45/55 to 55/45.

14. (Canceled)

15. (Currently Amended) The disposable diaper according to claim [[1,]] 10, wherein

each of said standing gathers has two or more elastic members.

16. (Previously Presented) The disposable diaper according to claim 15, wherein each

clastic member has a tensile load increase rate of 0.5 gf/% or lower from 20% extension ratio to

the respective effective extension ratio and a tensile load of 5 to 50 gf at the effective extension

ratio.

5 of 11 JWB/ETP